## **Technical Data Form**

# **LUBRATECH ULTRA PLUS XM 5W-30**



Synthetic Passenger Car Motor Oil

### **PRODUCT DESCRIPTION**

**LUBRATECH ULTRA PLUS XM 5W-30** is a high performance fully synthetic passenger car motor oil for long mileages. Designed for gasoline, diesel passenger cars and light duty vehicles equipped with after treatment devices such as diesel particulate filters (DPF). It decreases fuel consumption and it is environment friendly due to minimum levels of emissions with its mid SAPS property.

#### **PROPERTIES**

- Service, maintenance costs decreased due to longer periods of filling.
- Decrease emissions with its advanced formulation.
- Decrease fuel consumption, extend life of DPF.
- Excellent cold start ability due to excellent viscosity properties.
- With its fully synthetic advanced technology it protects the engine from wear, rust and corrosion.
- Effectively cleans the motor in higher temperatures, minimising deposit.

#### **MEETS REQUIREMENTS**

API: SN/CF

ACEA C3-12

GM dexos 2

BMW Long Life-04

#### **APPROVALS**

MB-Approval 229.52
 (Can also be used where MB 229.31 or MB 229.51 oil is required)

### **TECHNICAL INFORMATION**

Kinematic Viscosity	Viscosity Index (min)	Flash Point	Pour Point
100°C (cSt)		(min) (°C)	(max) (°C)
9,3 – 12,6	150	230	-32

Values can change for each production.

#### **STORAGE**

- Keep away from sources of ignition, store this product in a dry location where it can be protected from the elements.
- Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.
- All packs should be on pallets and maximum 2 rows on top of each other should be placed.
- Packs should be kept clean and dust should be taken care of with clean cloth.
- In open lubrication processes, tray should be kept under drainages. Empty packs should not be used except storage of lubricants.

### **WARNINGS and RECOMMENDATIONS**

- Waste products should not be spilled to any water sources or sewage or to dustbin.
- Contact with the product could cause skin problems, sterile gloves should be used.
- If it contacts with the skin, that region should be washed with water and soap.
- Doctor be should contacted in case of any skin irritation and redness.

The information in this TDS is obtained from reliable sources of OEM. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This TDS was prepared and is to be used only for this product. If the product is used as a component in another product, this information may not be applicable.

Product Name: LUBRATECH ULTRA PLUS XM 5W-30

First Published: 27.09.2019

FR.31

Revised Date: -Revise No: -