

PRODUCT DESCRIPTION

LUBRATECH ULTRA 0W-20 is a high performance synthetic motor oil for passenger cars. It is formulated for latest motor technologies. It is used in gasoline engines with or without turbos and catalytic converter where a fuel economy oil is recommended. It has been developed with special additives, which provide optimal protection during extended drain intervals.

PROPERTIES

- Lower fuel consumption
- High viscosity index and high resistance against shearing
- Fast cold start properties that results in less wear due to stable lubricant film
- Very good anti-wear, anti-corrosion, anti-foam properties
- Great dispersant and detergent properties providing a clean operation

MEETS REQUIREMENTS

- API SP (RC)
- GM dexos1 Gen2
- Ford WSS-M2C947-A
- ILSAC GF-6A & B
- Chrysler MS6395

TECHNICAL INFORMATION

Property	Test Method	Unit	Typical
Kinematic Viscosity 100°C	ASTM D 445	cst	7,5
Kinematic Viscosity 40°C	ASTM D 445	cst	41,5
Viscosity Index (min)	ASTM D 2270	-	160
Flash Point (min) (°C)	ASTM D 92	°C	229
Pour Point (max) (°C)	ASTM D 97	°C	-36
Density at 15 °C	ASTM D 4052	g/mL	0,85

Values can change for each production.

STORAGE

- Keep away from sources of ignition, store this product in a dry location where it can be protected from the elements.
- Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.
- All packs should be on pallets and maximum 2 rows on top of each other should be placed.
- Packs should be kept clean and dust should be taken care of with clean cloth.
- In open lubrication processes, tray should be kept under drainages. Empty packs should not be used except storage of lubricants.

WARNINGS and RECOMMENDATIONS

- Waste products should not be spilled to any water sources, sewage or to dustbin.
- Contact with the product could cause skin problems, sterile gloves should be used.
- If it contacts with the skin, that region should be washed with water and soap.
- Doctor be should contacted in case of any skin irritation and redness.

The information in this TDS is obtained from reliable sources of OEM. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This TDS was prepared and is to be used only for this product. If the product is used as a component in another product, this information may not be applicable.