

Former Name : Lubratech Ultra Plus X 10W-60

PRODUCT DESCRIPTION

LUBRATECH ULTRA 10W-60 is a fully synthetic high performance top level engine oil.

Specially developed for 4-stroke engines operating under extremely severe conditions of racing competitions. It has been specially developed for all modern turbo-charged, high output gasoline engines and some diesel engines of cars used in high performance passenger cars as well as SUVs, light vans and trucks. It is designed to provide excellent engine cleanliness and wear protection.

PROPERTIES

- Outstanding thermo-oxidative stability reduces deposits & sludge
- Superior anti-wear technology provides excellent wear protection under all conditions
- Active cleaning agents ensure maximum engine cleanliness resulting in trouble free engine operation
- Excellent low temperature fluidity aids quick cold start and provides wear protection at start-up

MEETS AND CERTIFICATES

- API SN/CF
- ACEA A3/B4

TECHNICAL INFORMATION

Property	Test Method	Unit	Typical
Kinematic Viscosity 100°C	ASTM D 445	cst	22,8
Kinematic Viscosity 40°C	ASTM D 445	cst	159
Viscosity Index (min)	ASTM D 2270	-	182
Flash Point (min) (°C)	ASTM D 92	°C	225
Pour Point (max) (°C)	ASTM D 97	°C	-39
Density at 15 °C	ASTM D 4052	g/mL	0,86

Values can change for each production.

STORAGE

- Keep away from sources of ignition, store this product in a dry location where it can be protected from the elements.
- Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.
- All packs should be on pallets and maximum 2 rows on top of each other should be placed.
- Packs should be kept clean and dust should be taken care of with clean cloth.
- In open lubrication processes, tray should be kept under drainages. Empty packs should not be used except storage of lubricants.

WARNINGS and RECOMMENDATIONS

- Waste products should not be spilled to any water sources, sewage or to dustbin.
- Contact with the product could cause skin problems, sterile gloves should be used.
- If it contacts with the skin, that region should be washed with water and soap.
- Doctor be should contacted in case of any skin irritation and redness.

The information in this TDS is obtained from reliable sources of OEM. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This TDS was prepared and is to be used only for this product. If the product is used as a component in another product, this information may not be applicable.